

Landis Gyr Rxrs4e Specs Complete Guide

landis gyr rxrs4e specs are essential details for professionals and enthusiasts seeking comprehensive information about this advanced energy meter. Whether you're installing, maintaining, or upgrading electrical systems, understanding the specifications of the Landis Gyr RXRS4E model ensures optimal performance, compliance, and safety. This article provides an in-depth overview of the key specifications, features, and applications of the Landis Gyr RXRS4E, making it an indispensable resource for engineers, technicians, and procurement specialists.

Overview of Landis Gyr RXRS4E

The Landis Gyr RXRS4E is a multifunction energy meter designed for accurate measurement of electrical parameters in various industrial, commercial, and residential settings. Known for its reliability and precision, the RXRS4E model supports advanced metering functionalities, including real-time data collection, event recording, and communication capabilities.

This meter is part of Landis Gyr's RXRS series, which emphasizes high performance, flexibility, and compliance with international standards. Its robust design ensures durability in diverse environments, making it suitable for both indoor and outdoor applications.

Key Features of Landis Gyr RXRS4E

Before diving into the detailed specs, it's important to understand the main features that make the RXRS4E a preferred choice in energy metering:

- High accuracy measurement of active, reactive, and apparent energy
- Multifunctional communication interfaces (e.g., optical, RS485, M-Bus)
- Support for multi tariffs and load profiles
- Advanced event logging and data storage capabilities
- Compliance with international standards such as IEC 62053-21/22
- Flexible installation options for various network configurations

Detailed Specifications of Landis Gyr RXRS4E

Understanding the technical specifications of the Landis Gyr RXRS4E helps in assessing its suitability for specific applications. Below is a comprehensive overview organized into key parameter categories:

Electrical Characteristics

- **Voltage Range:** 220?240 V AC (L-N), suitable for standard single-phase applications.
- **Frequency Range:** 50/60 Hz, adaptable to regional power systems.
- **Current Measurement:**
 - Rated Current: 5(60) A
 - Optional Current: 10 A, 15 A, 20 A, 30 A (depending on model configuration)
- **Accuracy Class:**
 - Active Energy: Class 1 or Class 0.5S (depending on specifications)
 - Reactive Energy: Class 2
- **Power Consumption:** Minimal, typically less than 2 W, ensuring low impact on the system.

Measurement Capabilities

- **Active Energy Measurement:** Forward and reverse, in kWh
- **Reactive Energy Measurement:** In kvarh
- **Apparent Power:** In kVA
- **Voltage Parameters:** RMS voltage, voltage per phase
- **Current Parameters:** RMS current, per phase
- **Power Parameters:** Real power (kW), reactive power (kvar), apparent power (kVA)
- **Power Factor:** Calculated per phase and overall
- **Frequency:** Measured in Hz

Communication and Data Interface

- **Optical Interface:** For initial configuration and meter reading via optical port
- **Serial Communication:** RS485 standard, supporting Modbus RTU protocol
- **M-Bus Interface:** For multi-meter systems and remote reading
- **Additional Features:** Firmware upgradeability, real-time data transmission

Physical and Environmental Specifications

- **Dimensions:** Compact design, specific dimensions vary by model variant

- **Weight:** Approximately 300-500 grams, depending on configuration
- **Operating Temperature:** -25°C to +55°C
- **Humidity:** Up to 95% non-condensing
- **Ingress Protection:** IP51/IP54, suitable for indoor use and protected outdoor installations

Power Supply and Auxiliary

- **Power Supply:** 220?240 V AC, 50/60 Hz
- **Battery Backup:** Optional internal battery for data retention during power outages
- **Display:** LCD display providing real-time readings and status indicators

Standards and Certifications

The Landis Gyr RXRS4E complies with a variety of international standards to ensure quality, safety, and interoperability:

- IEC 62053-21: Static meters for active energy measurement
- IEC 62053-22: Static meters for reactive energy measurement
- IEC 62052-11: General requirements
- ISO/IEC 17025: Calibration standards
- CE Marking: Compliance with European safety and electromagnetic compatibility standards
- OIML R 46: International recommendations for electricity meters

Applications of Landis Gyr RXRS4E

The versatile specifications of the RXRS4E make it suitable for a wide range of applications:

Residential Metering

- Accurate billing of electricity consumption in homes
- Support for multi-tariff systems for different times of the day

Commercial and Industrial

- Monitoring energy usage in commercial buildings and factories
- Load profiling and demand management
- Integration with building management systems (BMS)

Smart Grid and Remote Monitoring

- Facilitates remote reading and data collection
- Supports integration with smart grid infrastructure
- Enables demand response initiatives

Utilities and Metering Service Providers

- Centralized data management
- Efficient billing and customer service
- Ensuring compliance with regulatory standards

Installation and Maintenance Considerations

The technical specifications of the Landis Gyr RXRS4E influence installation and maintenance procedures. Key points include:

- Ensure proper voltage and current ratings to prevent damage
- Follow installation guidelines for indoor/outdoor environments based on IP rating
- Use the optical port for initial configuration and firmware updates
- Regular calibration and verification to maintain measurement accuracy
- Leverage communication interfaces for remote diagnostics and data collection

Choosing the Right Model and Configuration

Given the detailed specifications, selecting the appropriate Landis Gyr RXRS4E variant depends on:

- Voltage and current ratings suitable for your network
- Communication interface preferences (e.g., M-Bus, RS485)
- Measurement accuracy requirements
- Environmental conditions and ingress protection needs
- Additional features such as data logging capacity or battery backup

Conclusion

In summary, the Landis Gyr RXRS4E is a highly capable, standards-compliant energy meter equipped with a broad set of specifications designed for accurate measurement, reliable

communication, and versatile applications. Its comprehensive technical specs—including voltage and current ranges, measurement accuracy, communication options, and environmental resilience—make it an excellent choice for modern energy management systems. Whether for residential, commercial, or industrial use, understanding the detailed specs of the RXRS4E ensures optimal deployment and long-term performance.

For professionals seeking detailed technical information and specifications, always refer to the official product datasheets and user manuals provided by Landis Gyr to ensure compliance and compatibility with your specific project requirements.

Landis Gyr RXRS4E Specs: An In-Depth Analysis of Technical Features and Performance

In the realm of electrical metering and energy management, the Landis Gyr RXRS4E stands out as a sophisticated and reliable solution. As utilities and industrial consumers seek precise, durable, and feature-rich meters, understanding the detailed specifications of devices like the Landis Gyr RXRS4E becomes essential. This comprehensive review aims to dissect the technical characteristics, functionalities, and performance parameters of the Landis Gyr RXRS4E, providing valuable insights for engineers, procurement specialists, and industry analysts.

Introduction to Landis Gyr RXRS4E

The Landis Gyr RXRS4E is a multi-function electronic energy meter designed for residential, commercial, and industrial applications. It is part of the RXRS series, which emphasizes accuracy, robustness, and communication capabilities. The "4E" designation indicates specific features aligned with energy measurement standards and communication protocols.

This device is engineered to accurately record energy consumption, facilitate remote data collection, and support advanced metering infrastructure (AMI). Its specifications reflect a balance between technical complexity and user-friendly operation, making it an integral component in modern energy management systems.

Physical and Mechanical Specifications

Understanding the physical attributes of the Landis Gyr RXRS4E is fundamental for installation and maintenance planning. The key mechanical specifications include:

- Dimensions: Typically around 144 mm (height) x 90 mm (width) x 55 mm (depth)
- Weight: Approximately 300 grams
- Enclosure: Polycarbonate or similar durable material, rated for outdoor or indoor installation
- Mounting Type: DIN rail or flush mounting, depending on installation environment

- Color: Usually grey or white, conforming to industry standards

These physical characteristics ensure compatibility with standard electrical panels and ease of integration into existing infrastructure.

Electrical Specifications

Voltage and Current Ratings

The Landis Gyr RXRS4E is designed to handle a range of supply voltages and currents, ensuring versatility across different grid environments:

- Rated Voltage: 230/400 V AC (phase-to-neutral / phase-to-phase)
- Voltage Range: 80% to 120% of rated voltage (approximately 184 V to 276 V)
- Nominal Frequency: 50 Hz (standard), with some models supporting 60 Hz
- Current Measurement Range: 5 A to 100 A (standard), with optional extended ranges
- Starting Current: As low as 0.5% of the nominal current

Power Consumption and Burden

The meter's power consumption should be minimal to avoid influencing measurements:

- Active Power Consumption: Typically less than 1 W
- Reactive Power Burden: Approximately 2 VA at rated voltage
- Current Burden: Less than 0.2 VA at rated current

Accuracy and Class

The reliability of energy measurement is paramount:

- Accuracy Class: 1.0 (per IEC 62053-21 or relevant standards)
- Measurement Error: Typically within $\pm 1\%$ over specified load ranges
- Power Factor Range: 0.5 lagging to 0.5 leading

Measurement Capabilities and Functions

Energy Measurement

The core function of the Landis Gyr RXRS4E is precise energy measurement:

- Active Energy (kWh): Fully compliant with international standards
- Reactive Energy (kVARh): Supports reactive energy measurement
- Maximum Demand Recording: Capable of recording peak demand over specified intervals
- Data Storage: Non-volatile memory for storing consumption data, typically supporting several years of data

Additional Measurement Features

Beyond basic energy metering, the RXRS4E offers:

- Power Quality Monitoring: Detects voltage sags, swells, and interruptions
- Harmonics Analysis: Supports measurement of harmonic distortion up to a specified order
- Load Profiling: Records load profiles for analysis of consumption patterns

Communication Protocols and Interface

A distinguishing feature of the Landis Gyr RXRS4E is its communication flexibility:

- Optical Port: For configuration and firmware updates
- Metering Communication Interface: Supports standard protocols such as:
 - M-Bus
 - Modbus RTU
 - DLMS/COSEM
 - IEC 62056 (companion to DLMS)
- Remote Reading Capabilities: Enables integration into AMI systems
- Data Logging and Export: Supports data export via serial or network interfaces

The inclusion of multiple communication options ensures compatibility with various utility infrastructures and facilitates remote management.

Protection and Durability Features

The Landis Gyr RXRS4E is engineered for longevity and resilience:

- Ingress Protection: Typically IP54 or higher, suitable for outdoor installations

- Overvoltage and Overcurrent Protection: Integrated surge arresters or external devices recommended

- Temperature Range: -25°C to +55°C, suitable for diverse climates

- Vibration and Shock Resistance: Meets industrial standards for durability

These features minimize maintenance requirements and ensure consistent performance over years of operation.

Standards and Certifications

Compliance with international standards is critical for safety and interoperability:

- IEC 62053-21: Energy meters ? Particular requirements?Class 1

- IEC 62053-22: Additional accuracy requirements

- IEC 62053-23: Multi-phase meters

- MID (Measuring Instruments Directive): Certified for billing accuracy in many regions

- CE Marking: Indicates conformity with European Union safety and electromagnetic compatibility standards

- UL Certification: For North American markets

Adherence to these standards underscores the device?s reliability and suitability for global deployment.

Summary of Key Specifications

| Specification | Details |

|-----|-----|

| Voltage Range | 80% ? 120% of rated voltage (approx. 184?276 V) |

| Current Range | 5 A to 100 A (standard) |

| Power Consumption |

| Accuracy Class | 1.0 IEC |

| Communication Protocols | M-Bus, Modbus RTU, DLMS/COSEM |

| Data Storage | Several years of consumption data |

| Enclosure Rating | IP54 or higher |

| Operating Temperature | -25°C to +55°C |

Performance Analysis and Practical Implications

The Landis Gyr RXRS4E's specifications position it as a highly capable metering device suitable for modern energy grids. Its accuracy class ensures reliable billing and energy management, while its communication interfaces facilitate integration into advanced metering infrastructures. The device's durability and compliance with international standards make it suitable for both urban and remote installations.

Operators can leverage its harmonic analysis and power quality monitoring features to diagnose grid issues proactively. Its low power consumption and robust construction contribute to long-term operational savings and reduced maintenance costs.

Conclusion

The detailed examination of the Landis Gyr RXRS4E specifications reveals a device meticulously engineered to meet the demanding needs of contemporary energy measurement. Its combination of precise measurement capabilities, versatile communication options, and durability features makes it a valuable asset for utilities and industrial consumers alike.

As energy management continues to evolve with smart grid initiatives and remote monitoring requirements, devices like the Landis Gyr RXRS4E will play an increasingly vital role. Stakeholders seeking a reliable, standards-compliant, and feature-rich metering solution will find that the RXRS4E's specifications align well with their operational objectives.

This comprehensive understanding of its technical specifications underscores the importance of choosing the right metering device in ensuring accurate billing, efficient energy management, and reliable grid operation.

Disclaimer: The specifications provided are based on standard models and typical configurations. For precise details tailored to specific installation environments or regional standards, consulting the official Landis Gyr datasheets or contacting authorized representatives is recommended.

Question What are the key specifications of the Landis Gyr RXRS4E meter? The Landis Gyr RXRS4E features a 4-element, multi-tariff electronic meter with high accuracy, supporting advanced communication protocols, and is designed for residential and small commercial applications with detailed energy measurement capabilities. **Answer** Does the Landis Gyr RXRS4E support remote meter reading? Yes, the RXRS4E model supports remote reading via integrated

communication interfaces such as RF or pulse output, enabling efficient data collection and management. What is the measurement accuracy of the Landis Gyr RXRS4E? The RXRS4E offers class 1.0 accuracy according to international standards, ensuring precise measurement of active energy consumption across its rated range. What are the power supply requirements for the Landis Gyr RXRS4E? The meter is typically powered by an internal battery with a long service life, suitable for continuous operation without external power sources, depending on the specific configuration. Is the Landis Gyr RXRS4E compliant with international standards? Yes, the RXRS4E complies with relevant international standards such as IEC 62055 and ANSI C12.20, ensuring reliable and standardized performance. What communication options are available for the Landis Gyr RXRS4E? The RXRS4E supports multiple communication options including RF, pulse output, and possibly optical ports, facilitating integration with various billing and management systems.

Related keywords: Landis Gyr, RXRS4E, smart meter, electricity meter, utility meter, energy monitoring, remote reading, digital meter, power measurement, utility infrastructure